

ASME B36.19

Névleges csőméret	Külső átmérő			Schedule 5S			Schedule 10S			Schedule 40S			Schedule 80S		
				Falvastagság		Súly	Falvastagság		Súly	Falvastagság		Súly	Falvastagság		Súly
Coll	DN	in	mm	in	mm	kg/m	in	mm	kg/m	in	mm	kg/m	in	mm	kg/m
1/8"	6	0.405	10.30	-	-	-	0.049	1.24	0.28	0.068	1.73	0.37	0.095	2.41	0.47
1/4"	8	0.540	13.72	-	-	-	0.065	1.65	0.49	0.088	2.24	0.63	0.119	3.02	0.8
3/8"	10	0.675	17.15	-	-	-	0.065	1.65	0.63	0.091	2.31	0.84	0.126	3.2	1.1
1/2"	15	0.840	21.34	0.065	1.65	0.8	0.083	2.11	1	0.109	2.77	1.27	0.147	3.73	1.62
3/4"	20	1 050	26.67	0.065	1.65	1.03	0.083	2.11	1.28	0.113	2.87	1.69	0.154	3.91	2.2
1"	25	1 315	33.40	0.065	1.65	1.3	0.109	2.77	2.09	0.133	3.38	2.5	0.179	4.55	3.24
1 1/4"	32	1 660	42.16	0.065	1.65	1.65	0.109	2.77	2.7	0.14	3.56	3.39	0.191	4.85	4.47
1 1/2"	40	1 900	48.26	0.065	1.65	1.91	0.109	2.77	3.11	0.145	3.68	4.05	0.2	5.08	5.41
2"	50	2 375	60.33	0.065	1.65	2.4	0.109	2.77	3.93	0.154	3.91	5.44	0.218	5.54	7.48
2 1/2"	65	2 875	73.03	0.083	2.11	3.69	0.12	3.05	5.26	0.203	5.16	8.63	0.276	7.01	11.41
3"	80	3 500	88.90	0.083	2.11	4.51	0.12	3.05	6.45	0.216	5.49	11.29	0.3	7.62	15.27
3 1/2"	90	4 000	101.60	0.083	2.11	5.18	0.12	3.05	7.4	0.226	5.74	13.57	0.318	8.08	18.63
4"	100	4 500	114.30	0.083	2.11	5.84	0.12	3.05	8.36	0.237	6.02	16.07	0.337	8.56	22.32
5"	125	5 563	141.30	0.109	2.77	9.47	0.134	3.4	11.57	0.258	6.55	21.77	0.375	9.53	30.97
6"	150	6 625	168.28	0.109	2.77	11.32	0.134	3.4	13.84	0.28	7.11	28.26	0.432	10.97	42.56
8"	200	8 625	219.08	0.109	2.77	14.79	0.148	3.76	19.96	0.322	8.18	42.55	0.5	12.7	64.64
10"	250	10 750	273.05	0.134	3.4	22.63	0.165	4.19	27.78	0.365	9.27	60.31	0.5002	12 702	96 012
12"	300	12 750	323.85	0.156	3.96	31.25	0.18	4.57	36	0.3752	9 532	73 882	0.5002	12 702	132 082
14"	350	14 000	355.60	0.156	3.96	34.36	0.1882	4 782	41 302	-	-	-	-	-	-
16"	400	16 000	406.40	0.165	4.19	41.56	0.1882	4 782	47 292	-	-	-	-	-	-
18"	450	18 000	457.00	0.165	4.19	46.81	0.1882	4 782	53 262	-	-	-	-	-	-
20"	500	20 000	508.00	0.188	4.78	59.25	0.2182	5 542	68 612	-	-	-	-	-	-
22"	550	22 000	559.00	0.188	4.78	65.24	0.2182	5 542	75 532	-	-	-	-	-	-
24"	600	24 000	610.00	0.218	5.54	82.47	0.25	6.35	94.45	-	-	-	-	-	-
30"	750	30 000	762.00	0.25	6.35	118.31	0.312	7.92	147.36	-	-	-	-	-	-